

**ROPAC® MP 20LH pail**  
**UN Certified**  
**for dangerous solid goods**

**Technical Data Sheet**

**PACKAGING DESCRIPTION**

Commercial reference	ROPAC® MP 20L (pail). / ROPAC® MP 15-20 H (lid)
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADNR, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	319 mm (328 mm with handle)
External diameter at bottom	285,5 mm
Height incl. lid	355,5 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	1,61 cm <sup>3</sup> / day for 21% oxygen
UN certified for	II and III (group b and c of each class, excepted 1 and 2).
Packaging classification	Dangerous solid goods
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load: 201 kg / 24 H
Option	Flex-spout on lid



**PAIL CHARACTERISTICS**

Volume brim full	22,4 l
Volume under lid	22 l
UN certified for a maximum weight of content	27 kg
Weight	850 g
Internal diameter at top	303 mm
Internal diameter at bottom	281 mm
Embossing	Ⓢ 1H2/Y27/S/--/F/BVT 26087/SP
Decoration type	Digital print
Decoration area	On request
Standard palletisation (Euro pallet 120x80 cm)	120 pails (8 piles of 15 pails)
Height of pallet	1,79 m



**LID CHARACTERISTICS**

Weight	240 g (without gasket)
Diameter	300,5 mm
Embossing	Ⓢ MP 15-20H
Gasket	PVC
Standard palletisation (Euro pallet 120x80 cm)	480 lids (8 piles of 60 lids)
Height of pallet	1,75 m

*These specifications are without legal warranty and subject to changes without notification.*

February 2007 - SV

SCHOELLER ARCA SYSTEMS SWISS AG  
 11, rte de la Condémine  
 CH-1680 Romont  
 Tel.+41 26 651 92 11  
 Fax+41 26 651 92 31  
 info.romont@schoellerarca.com  
 www.schoellerarca.com



**Schoeller Arca Systems**

Creative solutions for better returns