

ROPAC® MP 5LH pail
UN Certified
for dangerous solid goods

Technical Data Sheet

PACKAGING DESCRIPTION	
Commercial reference	ROPAC® MP 5L (pail). / ROPAC® MP 3-6 H (lid)
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADNR, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	218 mm (222 mm with handle)
External diameter at bottom	178 mm
Height incl. lid	219.5 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	0,70 cm ³ /day for 21% oxygen
UN certified for	II and III (group b and c of each class, excepted 1 and 2).
Packaging classification	Dangerous solid goods
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load: 78kg
Option	Flex-spout on lid



PAIL CHARACTERISTICS	
Volume brim full	5,5 l
Volume under lid	5,3 l
UN certified for a maximum weight of content	6 kg
Weight	290 g
Internal diameter at top	200,5 mm
Internal diameter at bottom	176 mm
Embossing	① 1H2/Y6/S/-- /F/BVT260829/SCHOELLER WAVIN SYSTEMS AG
Decoration type	Digital print
Decoration area	On request
Standard palletisation (Euro pallet 120x80 cm)	528 pieces (16 piles of 33 pieces)
Height of pallet	2,03 m



LID CHARACTERISTICS	
Weight	91 g (without gasket)
Diameter	201,7 mm
Embossing	② MP3-6 H
Gasket	PVC
Standard palletisation (Euro pallet 120x80 cm)	1584 pieces (6 boxes)
Height of pallet	1,87 m

These specifications are without legal warranty and subject to changes without notification.

February 2007- SV

SCHOELLER ARCA SYSTEMS SWISS AG
 11, rte de la Condémine
 CH-1680 Romont
 Tel.+41 26 651 92 11
 Fax+41 26 651 92 31
 info.romont@schoellerarca.com
 www.schoellerarca.com



Certification



Schoeller Arca Systems

Creative solutions for better returns